

**CERTIFICATE OF
ANALYSIS**

Ulsan Synthetic Resin Plant
260-257, Cheoyong-ro, Nam-Gu,
Ulsan, Korea
Tel : 82-52-279-8829 / 8852 / 8857
Fax : 82-52-279-8840

Issuing Date	: 2022-03-16	Certification No	: URE220302027
User	: 주식회사 로즈메이	Order No	: 1335590
Grade	: ABS 750 N SW 25KG S BAG	Load No	: 82855072
Quantity	: 19,000 (KG)	Batch No	: 2231132SWX

Analysis Item	Unit	Spec.	Results	Test Method
NOTCHED IZOD IMPACT STRENGTH (6.4mm, 23℃)	kg.cm/cm	18 ~ 22	20.0	ASTM D256
TENSILE STRENGTH (50mm/min, Yield)	kgf/cm ²	450 ~ 500	459.3	ASTM D638
MELT FLOW INDEX (220℃ x 10.0KG)	g/10min	30 ~ 40	36.1	ASTM D1238

REFERENCE

I hereby certify that the result of analysis conforms to our standard specification

* KKPC Global Certified Systems
(Quality) ISO 9001, ISO/IATF 16949
(Environment) ISO 14001, ISO 45001



Kyong Po, Kim
General Manager , QA Team
Ulsan Resin Plant

**CERTIFICATE OF
ANALYSIS**

Ulsan Synthetic Resin Plant
260-257, Cheoyong-ro, Nam-Gu,
Ulsan, Korea
Tel : 82-52-279-8829 / 8852 / 8857
Fax : 82-52-279-8840

Issuing Date	: 2022-03-16	Certification No	: URE220302027
User	: 주식회사 로즈메이	Order No	: 1335590
Grade	: ABS 750 N SW 25KG S BAG	Load No	: 82848893
Quantity	: 19,000 (KG)	Batch No	: 2231232SWX

Analysis Item	Unit	Spec.	Results	Test Method
NOTCHED IZOD IMPACT STRENGTH (6.4mm, 23℃)	kg.cm/cm	18 ~ 22	20.7	ASTM D256
TENSILE STRENGTH (50mm/min, Yield)	kgf/cm ²	450 ~ 500	457.0	ASTM D638
MELT FLOW INDEX (220℃ x 10.0KG)	g/10min	30 ~ 40	35.0	ASTM D1238

REFERENCE

I hereby certify that the result of analysis conforms to our standard specification

* KKPC Global Certified Systems
(Quality) ISO 9001, ISO/IATF 16949
(Environment) ISO 14001, ISO 45001



Kyong Po, Kim
General Manager , QA Team
Ulsan Resin Plant

**CERTIFICATE OF
ANALYSIS**

Ulsan Synthetic Resin Plant
260-257, Cheoyong-ro, Nam-Gu,
Ulsan, Korea
Tel : 82-52-279-8829 / 8852 / 8857
Fax : 82-52-279-8840



Issuing Date	: 2022-03-16	Certification No	: URE220302027
User	: 주식회사 로즈메이	Order No	: 1335590
Grade	: ABS 750 N SW 25KG S BAG	Load No	: 82855073
Quantity	: 19,000 (KG)	Batch No	: 2231332SWX

Analysis Item	Unit	Spec.	Results	Test Method
NOTCHED IZOD IMPACT STRENGTH (6.4mm, 23℃)	kg.cm/cm	18 ~ 22	20.7	ASTM D256
TENSILE STRENGTH (50mm/min, Yield)	kgf/cm ²	450 ~ 500	461.4	ASTM D638
MELT FLOW INDEX (220℃ x 10.0KG)	g/10min	30 ~ 40	34.7	ASTM D1238

REFERENCE

I hereby certify that the result of analysis conforms to our standard specification

* KKPC Global Certified Systems
(Quality) ISO 9001, ISO/IATF 16949
(Environment) ISO 14001, ISO 45001

Kyong Po, Kim
General Manager , QA Team
Ulsan Resin Plant